PTFE porous film SEF-010, SEF-020, SEF-010(HB), SEF-110, PTFE porous sheet SEF-200, CHUKOH CHEMICAL INDUSTRIES, LTD. 1-Apr-2022 1 / 6

Safety Data Sheet (SDS)

Date prepared 5-Feb-2016 Date revised 1-Apr-2022

Applicable products	C-porous™ PTFE porous film SEF-010, SEF-020, SEF-010(HB), SEF-110 C-porous™ PTFE porous sheet SEF-200	
1. Product and company identification	ation	
·····	Product name	See the applicable products above.
	Product code Company name Address	- CHUKOH CHEMICAL INDUSTRIES, LTD. ATT New Tower 10F, 2-11-7, Akasaka, Minato-ku, Tokyo
	Telephone Fax Recommended use Restrictions on use Information on domestic manufacturers, etc.	03-6230-4414/81-3-6230-4417 03-6230-4413/81-3-6230-4446 For industrial use For industrial use See above
2. Hazards identification		
GHS Classification GHS label elements		Not applicable
Pictures or symbols		No information available
Warning statements		No information available
Hazard information		No information available
Cautionary statements Other hazards not related to o addressed by the GHS classification	pr	No information available No information available
Summary of important indicati and possible emergencies	ons	No information available
Other		Not hazardous under normal handling. Heating fluorocarbon resin produces pyrolysis products (fumes), which may cause eye, nose, and lung irritation if inhaled.

3. Composition/information on ingredients Substance/Mixture

Substance

	O	Reference No. in gazetted list in Japan		
Chemical name or generic name	Concentration or concentration ranges	Chemical Substances Control Law	Industrial Safety and Health Act	
Polytetrafluoroethylene (PTFE)	100%	6-939	6-939	9002-84-0

Ingredients contributing to GHS classification

No information available

4. First-aid measures

Inhalation

If fumes from heating or burning are inhaled, remove to fresh air and keep at rest in a position comfortable for breathing.

Seek medical advice/attention if you feel unwell.

PTFE porous film SEF-010, SEF-020, SEF-010(HB), SEF-110, PTFE porous sheet SEF-200, CHUKOH CHEMICAL INDUSTRIES, LTD. 1-Apr-2022 2 / 6

	PIFE porous film SEF-010, SEF-020, S	SEF-010(HB), SEF-110, PIFE poi	rous sheet SEF-200, CHUKOH CHEMICAL INDUSTRIES, LTD. 1-Apr-2022 2
	Skin contact		Wash with plenty of soap and water. If molten polymer contacts skin, cool rapidly with cold water. Do not attempt to peel polymer from skin. Seek medical advice/attention if irritation occurs.
	Eye contact		Flush eyes cautiously with water for several minutes. Seek medical advice/attention if irritation persists.
	Ingestion		Rinse mouth. Seek medical advice/attention if you feel unwell.
	The most important manifestat delayed symptoms	tions of acute and	No information available
	Precautions necessary for the who provide first-aid measures		No information available
	Special precautions for physici	ans	No information available
5.	Fire-fighting measures		
	Appropriate fire extinguishing r	nedia	Use extinguishing media appropriate for surrounding fire: Water, foam, powder, etc.
	Fire extinguishing media that s case of fire	hould not be used in	No information available
	Specific fire hazards		This product hardly flammable. Fire may produce irritating, corrosive, and/or toxic gas.
	Specific fire extinguishing meth	nods	Move product from fire area if you can do so without risk. Fight fire from maximum distance and use unmanned hose holders or monitor nozzles.
	Special protective equipment a firefighters	and precautions for	Wear self-contained breathing apparatus (SCBA). Firefighters should wear protection clothing and self- contained breathing apparatus (SCBA).
	Cautions		When fluorocarbon resin is exposed to high temperatures, it produces harmful particulates, fumes, and gases. In case of fire, evacuate upwind as far as possible to avoid inhalation.
6.	Accidental release measures		
	Personal precautions, protective emergency procedures	ve equipment and	Wear suitable protective equipment (see Section 8, Exposure controls/personal protection) to prevent inhalation and exposure of eyes or skin.
	Environmental precautions		Avoid discharge to rivers and environmental effects.
	Methods and materials for con	tainment and cleaning up	Break into small pieces. Collect if scatter. Dispose in accordance with Section 13.
	Measures to prevent secondar	y accidents	No information available
7.	Handling and storage		
	Handling	Technical measures	Install equipment in Section 8, Exposure controls/personal protection. Wear protective equipment.
		Precautions for safe handling	Prohibit the use of heat, sparks, and fire in the surrounding area. Watch out for fire. Do not carry cigarettes, cigars or tobaccos and do not smoke in the workplace as decomposition gas may be inhaled by smoking if the substance contacts them. Ensure good ventilation/exhaustion. Avoid breathing dust/fume. Wash hands thoroughly after handling.

PTFE porous film SEF-010, SEF-020,	SEF-010(HB), SEF-110, PTFE por	rous sheet SEF-200, CHUKOH CHEMICAL INDUSTRIES, LTD. 1-Apr-2022 3
	Avoidance of contact Hygiene measures	See Section 10, Stability and reactivity. Wash hands thoroughly after handling.
Storage		
	Conditions for safe storage	Stable at normal storage conditions. Storage at or below 25°C and 60% RH is preferred. Keep away from oxidizing agents.
	Safe containers and packaging materials	No restriction for packaging materials. Use containers which will not be broken.
8. Exposure controls/personal pr	atection	
Control concentration	otection	No settings
Allowable concentration		No settings
Engineering measures		In a process to heat over 260°C, good ventilation is necessary and also local exhaust equipment is to be installed.
Protective equipment		
	Respiratory protection	Wear appropriate respiratory protection if ventilation is not enough.
	Hand protection	Wear eye protection.
	Eye protection	Wear personal protective equipment including protective clothing and protective mask if necessary.
	Skin and body protection	Wear personal protective equipment including protective clothing and protective mask if necessary.
9. Physical and chemical properti	es	
Appearance		
	Physical state	Solid
	Color	White
Odor		Odorless
Melting point/freezing point		Not available
Boiling point, initial boiling point, and boiling range		Not available
Flammability		Flame Retardancy
Lower explosion limit and upper explosion limit/flammable limit		
	Lower	Not available
	Upper	Not available
Flash point		Not available
Autoignition temperature		Not available
Decomposition temperature		Not available
рH		Not available
Viscosity		Not available
Solubility		Insoluble in water
Partition coefficient (n- octanol/water)		Not available
Vapor pressure		Not available
Density and/or relative densit	су	0.17-0.99g/cm³

PTFE porous film SEF-010, SEF-020, SEF-010(HB), SEF-110, PTFE porous sheet SEF-200, CHUKOH CHEMICAL INDUSTRIES, LTD. 1-Apr-2022 4 / 6

PTFE porous film SEF-010, SEF-020, SEF-010(HB), SEF-110, PTFE porous sheet SEF-200, CHUKOH CHEMICAL INDUSTRIES, LTD. 1-Apr-202		
Relative gas density		Not available
Particle characteristics		Not applicable
Other data		Not available
10. Stability and reactivity		
Reactivity		Hazardous reactions will not occur under normal
		conditions.
		Begins to decompose, very slowly, at temperatures above 260°C. Thermal decomposition is more rapid at
		temperatures above 400°C.
Chemical stability		Stable under normal storage and handling conditions.
Onemical stability		May react with metal powders such as aluminum and
		magnesium or with fluorine compounds such as fluorine
		and chlorine trifluoride, and cause fire and explosion.
Possibility of hazardous rea	ctions	Hazardous reaction or polymerization generating
		excessive pressure/heat will not occur.
Conditions to avoid		Heat. Contact with incompatible materials.
Incompatible materials		Metal powders such as aluminum and magnesium or
·		fluorine compounds such as fluorine and chlorine
		trifluoride.
Hazardous decomposition p	roducts	Thermal decomposition of this product may evolve the following decomposition products at the following
		temperatures: Carbonyl fluoride and hydrogen fluoride
		(above 400° C). Tetrafluoroethylene (above 430° C).
		Hexafluoropropylene (above 440°C). Perfluoroisobutylene (above 475°C).
11 Taula da via di informa di an		
11. Toxicological information Acute toxicity		
	Oral	LD50 in mouse : 1,250mg∕kg
		LD50 in rat : 12,500mg∕kg
	Dermal	Not available
	Inhalation (vapor) Inhalation (dust)	Not available Not available
Skin corrosion/irritation	Initial con (dust)	Not available
Serious eye damage/eye ir	ritation	Not available
Respiratory or skin sensitiz	ation	Not available
Germ cell mutagenicity Carcinogenicity		Not available Not available
Reproductive toxicity		Not available
Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure)		Not available
		Not available
Swallowing hazard		Not available
Others		n of fluoropolymers may generate polymer fumes, hydrogen
	fluoride, carbonyl fluor follows.	ide, and perfluoroisobutylene. The toxicity information is as
	Effects on health	Inhalation of fumes from burning may produce polymer
		fume fever, a temporary flu-like condition with fever,
		chills and cough. This may last for a whole day and night.
		Skin absorption will not occur. There are no reports of
		sensitization.

FIFE porous min SEF-010, SEF-020,	SEF-010(HB), SEF-110, FIFE	borous sheet SEF 200, CHOROH CHEMICAL INDUSTRIES, LTD. TAPI-2022 J	
	Effects of hydrogen fluoride	Inhalation of low concentrations of hydrogen fluoride can initially include symptoms of choking, coughing, and severe eye, nose, and throat irritation, fever, chills for one to two days, followed by difficulty in breathing, cyanosis, and pulmonary edema. Overexposure to hydrogen fluoride can injure the liver and kidneys.	
	Effects of carbonyl fluoride	Skin: Irritation with discomfort or rash Eye: Corrosion with corneal or conjunctival ulceration Upper respiratory passage: Irritation Lung: Temporary irritation effects with cough, discomfort, difficulty in breathing, or shortness of breath (Individuals with pre-existing diseases of the lungs may have increased susceptibility to the toxicity after excessive exposures to thermal decomposition products.)	
	Effects of perfluoroisobutylene	Even trace amounts are extremely toxic.	
12. Ecological information			
Ecotoxicity		Not available	
		Handle with care as leakage or disposal may affect the environment. In particular, take measures to prevent the product from flowing into the ocean via soil, drains and rivers.	
Persistence and degradability ecological accumulative property Mobility in soil Hazardous to the ozone layer		Not available Not available Not available Does not contain any substances that deplete the ozone layer listed in Annexes to the Montreal Protocol.	
13. Disposal considerations			
IS. Disposal considerations Information on safe and environmentally desirable disposal or recycling of chemicals, contaminated containers and packaging		Dispose in accordance with applicable laws and regulations and standards of local governments. Entrust the disposal to a licensed waste disposal contractor or a local public body who conducts the disposal. When entrusting the disposal to a disposal contractor, notify the danger and toxicity thoroughly to the contractor.	
Contaminated container and packaging		Dispose in accordance with applicable laws and regulations and standards of local governments.	
14 Turnen est in from th			
14. Transport information UN number		Not dangerous goods	
Item (UN transport name)		Not dangerous goods	
UN Classification		Not dangerous goods	
Container grade		Not dangerous goods	
marine pollutant		Not dangerous goods	
Liquid substances transported in bulk according to MARPOL 73/78 Annex II and IBC Code		Not dangerous goods	

PTFE porous film SEF-010, SEF-020, SEF-010(HB), SEF-110, PTFE porous sheet SEF-200, CHUKOH CHEMICAL INDUSTRIES, LTD.			rous sheet SEF-200, CHUKOH CHEMICAL INDUSTRIES, LTD. 1-Apr-2022 6 $/$ 6
tra	pecial safety measures for ansportation or means of ansportation		Confirm that there is no damage, corrosion, or leakage of the containers before transportation. Avoid direct sunlight at transportation. Load containers not to cause damage, corrosion or leakage and thoroughly prevent load collapse. Do not stack heavy objects.
Re	egulatory information on domes	tic regulations, if any	Not applicable
15. R	egulatory information		
Ap	oplicable laws and regulations a	nd information on requi	rements imposed by such laws and regulations
	Pollutant Release and Transfer Register (PRTR)		Not applicable
	Industrial Safety and Health Law		Not applicable
	Poisonous and Deleterious Substances Control Act		Not applicable
re	ther applicable laws and gulations and information on quirements imposed by		Not applicable
16. O	ther information		
			Hazard statements herein are made based on the assumption of industrial use and general handling. Handle with care at the actual use by referring to the hazard statements herein.
		Restrictions on use	This product is not intended for medical use. Do not use this product for implant or in a way that will contact with the body fluid or tissue. Consult with us in advance if it is expected to use the product in medical field.
		References	SDS made by raw material manufacturers.

The information herein may be revised if any new findings are obtained.

Values of concentration and physical and chemical properties are not guaranteed values.

Hazards identification was prepared based on the documents, information and data available at the time of preparation, but it does not mean that all documents, information and data are covered.